

Teledyne Odom Hydrographic

# Hydrotrac II

Single-Frequency  
Portable Hydrographic  
Echo Sounder

## Precise Data Collection in Adverse Conditions

Specifically designed for work in less-than-ideal circumstances on small survey boats and inflatable watercraft, the HYDROTRAC™ II offers compact portability and the confidence of knowing you're using a proven Odom product. It is completely waterproof and comes equipped with the same advanced features you've come to trust and depend on in Odom echo sounders.



*Photo courtesy Pan Asia Engineering*

### PRODUCT FEATURES

- 8.5 in / 216mm thermal printer
- Annotation printed on chart
- LCD display (1 in. high)
- Optional internal GPS with WAAS
- Sealed keypad controls
- Manual/remote mark command
- Auto scale change (phasing)
- Separate adjustment for power and pulse width
- Heave input from motion sensor
- TVG curve for side scan and bathymetry
- Output: NMEA, ECHOTRAC, DESO 25, etc.
- Splashproof (with front cover in place)
- Fix mark annotation: date, time, fix no., depth and GPS (if input)
- Flash Memory upgrades by SD card
- Built-in simulator
- Full echogram output through Ethernet
- IP67



# Hydrotrac II

Single-Frequency Portable  
Hydrographic Echo Sounder



## TECHNICAL SPECIFICATIONS

<b>Frequency Agile</b>	Operator selectable through menu – 24, 28, 33, 40, 100, 120, 200, 210 and 340 kHz	
<b>Output Power</b>	600 watts	
<b>Power Requirement</b>	11-28 V DC	
<b>Resolution</b>	0.1 ft / 0.01m	
<b>Accuracy</b>	200 kHz – 1cm (0.1% of depth value (corrected for sound velocity)) 33 kHz – 10cm 0.1% of depth value (corrected for sound velocity)	
<b>Maximum Depth Range</b>	600m or 1800 ft.	
<b>Environmental</b>	Operating     0° - 45° C Storage        -20° - 45° C	
<b>Communication</b>	2 RS232 ports or 1 RS232 and 1 RS422 Ethernet port	8 bit data 1600 samples/ping
<b>Printer</b>	High resolution 8 dot/mm (203 dpi); 16 gray shades; 216mm (8.5 in) wide thermal paper; External ON/OFF switch; paper advance control	
<b>Dimensions</b>	368 mm (14.5 in) H x 419 mm (16.5 in) W x 203 mm (8 in) D	
<b>Weight</b>	22.5 lbs (10.2 kg)	
<b>Display Panel Layout</b>	4 Line x 20 character display OFF/STBY/LOW/MED/HI power settings Chart ON/OFF with LED inside Chart Advance Sensitivity	Chart Feed Separate panel overlays for display and chart controls Keypad (arrow keys) Power Gain
<b>Sensor I/O</b>	MRU Heave corrects data Outputs MRU data in Ethernet packet	Annotates chart Embeds position in Ethernet packet
<b>Software</b>	TOH's Windows based software included: eChart Display, Control & Logging Software	
<b>Options</b>	200 kHz or 340 kHz side scan transducer Wide selection of transducers Remote display Lid with window Transit case with wheels Internal GPS with WAAS differential corrections and PPS reference signal Antenna upgrade	



Photo courtesy Pan Asia Engineering



The HydroTrac II  
and optional lid  
with window



**TELEDYNE**  
**ODOM HYDROGRAPHIC**  
Everywhere you look™  
[www.odomhydrographic.com](http://www.odomhydrographic.com)

Teledyne Odom Hydrographic

1450 Seaboard Avenue, Baton Rouge, Louisiana 70810-6261 USA

Tel. +1-225-769-3051 Fax: +1-225-766-5122 Email: [odom@teledyne.com](mailto:odom@teledyne.com)

Specifications subject to change without notice.  
© 2014 Teledyne Odom Hydrographic, Inc. All rights reserved.